

TIMBERPRO

A Komatsu forestry brand

TB630D harvester



Photo may include optional equipment

Operating weight

61,020 lbs. (27,678 kg)

Rated horsepower

350 HP (261 kW) @ 1,800 rpm

Specifications

Engine

Model	Cummins L9	
Type	Water cooled, 4-cycle, XPI fuel system	
Aspiration	eVGT, after cooled	
No. of cylinders	6	
Bore	4.49 in	114 mm
Stroke	5.86 in	145 mm
Engine displacement	543 in ³	8.9 L
Horsepower		
SAE J1995	Rated 350 HP (261 kW) @ 1,800 rpm	
Fan drive type for radiator cooling	Hydraulic, variable speed, auto reverse	
Governor	All-speed control, electronic	

U.S. EPA Tier 4 Final emission certification

Hydraulic system

Type: load sense, pressure compensated, open loop system and dedicated closed loop systems

Hydraulic control modes	SAE/US/US mod, custom attachment settings	
Pumps	Implement, swing, attachment, travel, charge, fan, auxiliary	
Main pump type	Variable displacement piston type	
Maximum flow	110 gpm	418 L/min

Coolant (refilling) and lubricant capacity

Fuel tank	145 gal	548 L
Coolant	13.5 gal	51 L
Engine	6.25 gal	23.6 L
Hydraulic tank	64 gal	242 L
DEF tank	15 gal	56.8 L

Swing system

Drive method	Hydrostatic closed loop	
Swing reduction	Planetary gear	
Swing circle, lubrication	External tooth, greased	
Holding brake/swing lock	Oil bath multi-disk, spring applied, hydraulic release	
Swing speed	6.6 rpm	
Swing torque	54,334 lb-ft (73.67 kN/m)	
Maximum reach to pin	32' 1" (9,784 mm)	
Max working swath	See drawing on next page for details	
Max tail swing radius	5' 10" (1,778 mm)	
Working radius - minimum, @ 4' 11" (1.5 m) above ground	5' 5" (1,650 mm)	
Lift capacity @ 20' (6.1 m), @ 4' 11" (1.5 m) above ground	13,500 lbs. (6,123 kg)	
Bare pin lift at full reach, @ 4' 11" (1.5 m) above ground	6,000 lbs. (2,721 kg)	

Frame, drive and axles

Main frame type	Plate/box	
Axle type	Front: bogie axle (20 ton) Rear: single axle (18 ton)	
Drive/travel motor type	Hydrostatic	
Final drive	Planetary gear	
Maximum tractive effort	58,303 lbf	259.3 kN
Travel speed	Two speed ranges	
Parking brake method	Oil bath multi-disk holding brake, spring applied, hydraulic release	
Steering controls	Joystick	
Ground clearance at axle with standard tire	18"	457 mm
Standard tire size	Front: (4) 710/45 - 26.5 F2-800 Rear: (2) 750/55-26.5	
Optional tire size	Front: (4) 750/55 - 26.5 TRS-800 Rear: (2) 28L-26	
Frame articulation lock type	No frame articulation	



Operating weight

Machine configuration:




Forwarder boom
Telescopic arm
Harvester hydraulics

Operating weight	61,020 lbs.	27,678 kg
Front axle ground pressure - no attachment - transport position - std tire	10.95 psi	0.77 kg/cm ²
Rear axle ground pressure - no attachment - transport position - std tire	15.79 psi	1.11 kg/cm ²

Dimensions



Transport dimensions: See A, C, J and N



Dimensions and weights

A	Overall height for transport (std)	12' 5" (3,780 mm)
B	Ground clearance (axle, std tire)	18" (460 mm)
C	Overall transport width (rear tire narrow) (rear tire wide)	9' 8" (2,997 mm) 10' 5" (3,277 mm)
D	Ground clearance, articulation center (std tire)	20" (515 mm)
E	Distance between bogie hubs, (center to center)	5' 7" (1,690 mm)
G	Overall body width (widest point)	8' 7" (2,616 mm)
H	Tire track width, center to center	8' 3" (2,522 mm)
J	Height of arm off deck for transport	25" (635 mm)
K	Wheel base on ground (std)	17' 11" (5,461 mm)
L	Wheel base, overall (std tire, std frame)	22' 7" (6,883 mm)
M	Overall frame length	24' 10" (7,569 mm)
N	Overall length for transport (std tire, std frame)	33' 6" (10,211 mm)
P	Machine height, rear of rear frame (std tire, std single counter weight)	4' 2" (1,276 mm)
Q	Machine height, front frame tie down point (stepped frame) (std frame)	2' 11" (889 mm) 3' 5" (1,050 mm)
R	Min turning radius (std tire, wide installation, std frame)	R inside: 13' 6" (4,109 mm) R outside: 24' 11" (7,602 mm)
	Overall height highest point body	See dimension A

Range of motion chart TB630D harvester

A	41' (12,497 mm)
B	35' 3" (10,744 mm)
C	26' 1" (7,950 mm) @ 4' 11" (1.5 m) above ground
D	32' 1" (9,779 mm) @ 4' 11" (1.5 m) above ground

Equipment

Engine and related components

350 HP (261 kW) Cummins QSL9 (Stage V) engine	•
1,151 lb-ft (1,561 N-m) @ 1,800 rpm	
Single module DOC/DPF/SCR	•
eVGT, after cooled	•
Hydraulic variable speed cooling fan with auto reverse	•

Operator environment

ROPS/FOPS/OPS certified cabin with three egress routes	•
Continuous rotation swing upper	•
Digital climate control system, filtered fresh air intake and pressurized cabin	•
AM/FM/WB radio with Bluetooth® handsfree and USB input	•
IQAN MD4 HD control system with 10" touchscreen	•
Left and right joystick controls for machine operation	•
Coordinated boom operations	•
Standard seat - air ride and heated, with lumbar adjust	•
Deluxe seat - air ride, heated and cooled with lumbar adjust	○
Seat belt harness	•
Rear mounted camera system	•
Cup holder	•
Interior LED lights	•
English decals	•
Paint - TimberPro red	•
Paint - custom color	○

Serviceability

Rear opening powered hood to access engine bay and hydraulic components	•
Side access service doors	•
Hydraulic tank vacuum system	•
Electric hydraulic oil fill pump	•
Hydraulic reservoir oil level sight glass	•
Hydraulic low oil level warning indicator	•

Hydraulic system

Implement pump	○
Drive pump	•
Swing pump	•
Charge pump - gear pump	•
Charge filter non bypass, 6 micron	•
Return filters with bypass, 10 micron	•
Case drain filter with bypass, 10 micron	•
Hydraulic oil cooler	•

Electrical system

24V electrical system with battery disconnect	•
Alternator, 100 ampere, 24V	•
Batteries, 2 × 12V	•
Working lights - LED high-intensity lighting	•

Standard equipment •

Optional equipment ○

Drivetrain

Bogie, 20 ton	•
Single axle, 17 ton	•
Outboard planetary finals	•
Gearbox - dual speed hydrostatic	•
Internal wet multi-disk parking brake, hydraulic released	•

Guards and covers

Articulation stops for bogie axle	•
-----------------------------------	---

Tires

Front 710/45 - 26.5 F2-800 (standard)	•
Rear 750/55 - 26.5 TRS	•
710/45 - 26.5 TRS	○
750/55 - 26.5 ELS or TRS	○
Rear 28L - 26	○
Rim spacing - wide	•
Rim spacing - narrow	○

Front frame, rear frame

Standard front frame	•
Front frame, hydraulic dozer blade provision	○
Front frame, with hydraulic step	○
Standard rear frame	•

Work equipment - attachments

Forwarder boom with 25' 7" reach	•
Forwarder boom with 6' telescopic stick for 32' 1" reach (+6' over std)	•
Hydraulics for grapple, fixed stick	•
Hydraulics for other attachments	○
Heavy duty forwarder cylinder	○
Hultdins 360s, 420s and 520s grapple attachment options	○
Fixed heel, fixed stick	○
Fixed heel, telescopic stick	○
Combination attachment quick change stick boom adapter	○
Dozer blade	○

Optional equipment

Komtrax monitoring system	○
Fire suppression system	○
Diesel Espar pre-heater with timer	○
120V AC plug-in engine block pre-heaters	○
120V AC plug-in hydraulic tank heater	○
Uptime kit	○

TimberPro Inc reserves the right to change specifications without notice or obligation. Product illustrations may be equipped with optional equipment.

Product designs, specifications and/or data in this document are provided for informational purposes only and are not warranties of any kind. Product designs and/or specifications may be changed at any time without notice. The only warranties that apply to sales of products and services are Komatsu's standard written warranties, which will be furnished upon request.

Komatsu and other trademarks and service marks used herein are the property of Komatsu Ltd., Komatsu America Corp., Komatsu Mining Corp. Komatsu Germany, or one of their affiliates, or the respective owners or licensees.

KOMATSU

komatsu.com

